



*1: Dimensional allowance before slit machining.

- A clammer that joints 2 shafts at any angle.
- Clamping type for one side. Mounting shaft, removing shaft and angle adjustment are easy. Moreover this does not scratch the shaft.
- Convenient for fixing of side guide and sensors of the conveyance line.
- Compatible with both round shaft and square shaft.
- All products are provided with hex socket head cap screw and hex socket set screw.

Material/Finish



	FCFA
Main Body	Aluminum Alloy
Hex Socket Head Cap Screw	SUSXM7
Hex Socket Set Screw	SUSXM7
Joint Shaft	SUS304

Unit : mm

Part Number	Mass (g)	D1	D2	B1	B2	A	W	W1	P	H	F1	F4	F3	F2	M (Coarse)	M1 (Coarse)
FCFA-8C-8	83	8	8			22	63	28	45	11	3.7	25.8	15	7	M3	M4
FCFA-10C-10	80	10	10	8	8	22	63	28	45	11	3.7	25.8	15	7	M3	M4
FCFA-12C-12	118	12	12	10	10	25	72	32	51.5	12.5	3.8	30.2	17	8	M3	M5
FCFA-15C-15	216	15	15	12	12	30	90	40	64.5	15.5	4.5	38.5	21	10	M4	M5
FCFA-20C-20	433	20	20	16	16	38	113	50	80	20	5.5	48.5	27	13	M5	M5

• Recommended dimensional allowance of the shaft is g6. Use a long wrench to tighten the screw.

- Usage example
For fixing sensor.



Part number specification

FCFA-12C-12



Cleanroom Wash & Packaging	Screw Length Adjustment	Vibration Resistant	Laser Marking
Available / Add'l charge	Not Available	Please feel free to contact us	Available / Add'l charge