



● Application

Reducing the size of equipment and devices
Compact precision equipment

● Material/Finish



	SNZCXS
Main Body	SUSXM7 (Equivalent to SUS304)

● Part Number Specification

SNZCXS-M2-3



- M1.4-M2.5. Miniature screws for precision instruments.
- Flat head machine screw type with low head height. For space-saving of equipment/devices and applications with limited overhead space.
- Screw heads are unlikely to be damaged due to tightening, allowing safe and secure tightening to be performed.
- Install and remove with **SKX** Dedicated Wrench or **SKXB** Dedicated Bit and **SRD** Dedicated Magnetic Screwdriver together.

Part Number	Applicable Wrench	Applicable Bit
SNZCXS-M1.4	—	SKXB-3
SNZCXS-M1.6	SKX-4	SKXB-4
SNZCXS-M2	SKX-5	SKXB-5
SNZCXS-M2.5	SKX-6	SKXB-6

- Use the **SKX-N** hexalobular wrench for extremely limited access spaces for mounting and removing in tight spaces.
- We manufacture products with special specifications such as ventilation holes, cleanroom washing and special packaging.

Unit : mm

Part Number	M (Coarse)		L								D1	L1	Hexalobular Socket No.	t max.	Max. Torque (N·m)	Mass (g)	Qty per Pack
	Nominal of Thread	Pitch	2	3	4	5	6	8	10	2							
SNZCXS-M1.4	M1.4	0.3	2	3	4	5	6	8	10	2	0.5	3		0.25	0.07	0.024 - 0.09	50
SNZCXS-M1.6	M1.6	0.35	2	3	4	5	6	8	10	2.4	0.5	4		0.3	0.1	0.04 - 0.12	50
SNZCXS-M2	M2	0.4	2	3	4	5	6	8	10	3	0.6	5		0.35	0.22	0.062 - 0.2	50
SNZCXS-M2.5	M2.5	0.45		3	4	5	6	8	10	4	0.8	6		0.55	0.46	0.12 - 0.34	50

- When purchasing less volume than one full bag, a separate handling fee is charged. For details, see the Sold Separately Service.

● Related Products

SKX Hexalobular Wrench



SKXB Hexalobular Short Bit



SKX-N Hexalobular Wrench for Extremely Limited Access Spaces



SRD Magnet Screwdriver



1 Individual Sales	Cleanroom Wash & Packaging	Screw Length Adjustment	Vibration Resistant	Modification process for captive use
Available / Add'l charge	Available / Add'l charge	Not Available	Available / Add'l charge	Not Available