




SPFA-N Plastic Screws - Hex Nuts - PFA

Heat-resistance Chemical-proof



- PFA is a plastic with excellent heat resistance, electrical properties, chemical resistance, and abrasion resistance. Most chemicals cannot penetrate PFA.
- It has excellent non-adhesive and lubrication properties.
- It also has high flame retardance which clears the UL 94 V-0 standard.
- The properties and precautions of plastic screws
→ P.xxxx

Application

FPD production equipment / Semiconductor devices / Printed circuit board etching devices / Metallic surface treatment equipment and facilities / Chemical plants


Material/Finish

RoHS

	SPFA-N
Main Body	PFA (Perfluoroalkoxy Alkane) (Milky White)
Heat Resistance Temperature*1	260°C

* 1 : This is the value for the resin material. The operating temperature of the product changes with performance conditions such as tightening torque.

Unit : mm






Part Number 	M (Coarse)		B	T	Mass (g)	Qty per Pack
	Nominal of Thread	Pitch				
SPFA-M4-N	M4	0.7	7	3.2	0.22	10
SPFA-M5-N	M5	0.8	8	4	0.33	10
SPFA-M6-N	M6	1	10	5	0.67	10
SPFA-M8-N	M8	1.25	13	6.5	1.5	5

- When purchasing less volume than one full bag, a separate handling fee is charged. For details, see the Sold Separately Service.

Part number specification

SPFA-M4-N



 Individual Sales → P.xxxx	 Cleanroom Wash & Packaging → P.xxxx	 Screw Length Adjustment → P.xxxx	 Vibration Resistant → P.xxxx	 Modification process for captive use → P.xxxx
Available / Add'l charge	Available / Add'l charge	Not Available	Not Available	Not Available