e-nedzi.com

# SNSH-C276 Hex Socket Head Cap Screws (Hastelloy C - 276 equiv.)

Scleanroom wash & packaging 🖕 Chemical-proof



## Mechanical property

	Hastelloy (UNS N10276)	SUS304			
Tensile Strength (N/mm <sup>2</sup> )	690 or More	520 or More			
0.2% Proof Stress (N/mm <sup>2</sup> )	283 or More	205 or More			
Elongation (%)	40 or More	40 or More			

• Values in chart are for reference only. They are not guaranteed values.

#### Physical property

	Hastelloy (UNS N10276)	SUS304
Specific Gravity	8.89	7.93
Longitudinal Elastic Modulus (GPa)	205	193
Specific Heat (J/kg·K)	427	500
Electric Resistance ( $\mu \Omega \cdot m$ )	1.23	0.7
Linear Expansion Coefficient (K <sup>-1</sup> )	11.2×10 <sup>-6</sup>	17.3×10 <sup>-6</sup>

• Values in chart are for reference only. They are not guaranteed values.



- Hastelloy C-276 is a general type of Hastelloy.
- Excellent corrosion resistance against oxidizing and reducing salts.
- Cleanroom wash and cleanroom packing are completed.
- Also, SNSH-C22 Socket Head Screw-Hastelloy (Hastelloy C-22), which is also resistant to wet chlorine gas, hypochlorite, and chlorine dioxide is available.

## Application

FPD production equipment, semiconductor devices, printed circuit board etching devices, metallic surface treatment equipment and facilities, and chemical plants

<ul> <li>Material/Finish</li> </ul>	🖉 RoHS
	SNSH-C276
Main Body	UNS N10276(Hastelloy*1C-276 equiv.)

\*1: Hastelloy is a registered trademark of Haynes International, Inc.

	M (Coarse)	L 💶												Tension*1		
Part Number	Nominal of Thread ٵ	Pitch										D1	L1	В	Rupture Load (N)	Mass (g)
SNSH-M3-C276	M3	0.5	6	8	10	12	16	20				5.5	3	2.5	3980	0.81 - 1.6
SNSH-M4-C276	M4	0.7		8	10	12	16	20	25			7	4	3	6960	1.9 - 3.6
SNSH-M5-C276	M5	0.8			10	12	16	20	25			8.5	5	4	11200	3.1 - 5.4
SNSH-M6-C276	M6	1				12	16	20	25	30		10	6	5	15900	5.8 - 9.5
SNSH-M8-C276	M8	1.25					16	20	25	30	35	13	8	6	29000	14 - 22

\*1: Values in chart are for reference only. They are not guaranteed values.

# • Part number specification



Batch cleanroom packing is provided for orders containing multiple items of the same size.

1 Individual Sales 1 piece in 1 pack Screw Length Adjustment Vibration Resistant Modification process for captive use Cleanroom washed and packed Available / Add'l charge Available / Add'l charge Available / Add'l charge

▶ https://www.nbk1560.com