


SNS-EL Hex Socket Head Cap Screws - Electroless Nickel Plating









- Our unique processing technology enables screws to meet strength class 12.9 after surface treatment.
- For applications that require both high strength (Strength Class 12.9) and corrosion resistance.

Application

Equipment and device structures, FPD production equipment, semiconductor devices, and general industrial machines

Material/Finish



	SNS-EL
Main Body	SCM435 Electroless Nickel Plating
Strength Class	12.9

Unit:mm

Part Number	M (Coarse)		. 4	L 42										D ₁	1.	В	Mass (g)	Qty
	Nominal of Thread 📶	Pitch										וט	L1	D	iviass (g)	per pack		
SNS-M3-EL	M3	0.5	5	6	8	10	12	16	20					5.5	3	2.5	0.67 - 1.4	20
SNS-M4-EL	M4	0.7	5	6	8	10	12	16	20	25				7	4	3	1.4 - 3.2	20
SNS-M5-EL	M5	8.0		6	8	10	12	16	20	25				8.5	5	4	2.2 - 4.8	20
SNS-M6-EL	M6	1			8	10	12	16	20	25	30			10	6	5	4.3 - 8.3	10
SNS-M8-EL	M8	1.25				10	12	16	20	25	30	35		13	8	6	10 - 19	10
SNS-M10-EL	M10	1.5							20	25	30	35	40	16	10	8	23 - 33	10

• When purchasing less volume than one full bag, a separate handling fee is charged. For details, see the Sold Separately Service.

• Part number specification





