e-nedzi.com

SNSS-FC Hex Socket Head Cap Screws - Fluorine Coating

Seizing Prevention SUS Stainless steel

• Tightening property (reference) Part Number : SNSS-M5 - 25-FC





- Coating with good cost performance.
- Excellent lubricating ability and suitable for seizing prevention of screws.

Application

Seizing prevention FPD production equipment, semiconductor devices, and general industrial machines

| Material/Finish | 🚺 RoH |
|-------------------------------------|--|
| | SNSS-FC |
| Main Body | SUSXM7 (S.S. Grade : A2) Fluorine Coating |
| Strength Class | A2-70 |

| | | | | | | | | | | | | | | | | | | | Unit : mm |
|-------------|--------------------------------|-------|---|---------------------|---|----|----|----|----|----|----|----|-------|----------|----|-----|----------|-------|-----------|
| Part Number | M (Coarse) | | | | | | | | | | | | | D1 | 1. | в | Mass (g) | | Qty |
| | Nominal of Thread 1 | Pitch | | L 42 D1 L1 B Mass (| | | | | | | | | s (g) | per pack | | | | | |
| SNSS-M3-FC | M3 | 0.5 | 5 | 6 | 8 | 10 | 12 | 16 | 20 | | | | | 5.5 | 3 | 2.5 | 0.6 | 7-1.4 | 10 |
| SNSS-M4-FC | M4 | 0.7 | | 6 | 8 | 10 | 12 | 16 | 20 | 25 | | | | 7 | 4 | 3 | 1.5 | - 3.2 | 10 |
| SNSS-M5-FC | M5 | 0.8 | | | 8 | 10 | 12 | 16 | 20 | 25 | | | | 8.5 | 5 | 4 | 2.5 | - 4.8 | 10 |
| SNSS-M6-FC | M6 | 1 | | | | 10 | 12 | 16 | 20 | 25 | 30 | | | 10 | 6 | 5 | 4.7 | - 8.3 | 10 |
| SNSS-M8-FC | M8 | 1.25 | | | | | | 16 | 20 | 25 | 30 | 35 | | 13 | 8 | 6 | 12 | - 19 | 10 |
| SNSS-M10-FC | M10 | 1.5 | | | | | | | 20 | 25 | 30 | 35 | 40 | 16 | 10 | 8 | 23 | - 33 | 10 |

• When purchasing less volume than one full bag, a separate handling fee is charged. For details, see the Sold Separately Service.

• Part number specification



1 Individual Sales → Pxxxx S (Cleanroom Wash & Packaging → Pxxx) Serve Length Adjustment → Pxxx 2 Vibration Resistant → Pxxx Modification process for captive use → Pxxx Available / Add'l charge Not Available Not Available Not Available Please feel free to contact us

