




# SWUT Hex Lock Nuts - Titanium

Cleanroom wash &amp; packaging

Non-Magnetic

Lightweight

Vibration resistant treatment



- Specific gravity is approximately 60% of stainless steel.
- These nuts are equipped with vibration resistant patch to prevent screw from loosening.
- Continuous Max. Operating Temperature :  
-40 to 120 deg C

## ● Application

Lightweight applications in automobiles, aircrafts, spacecrafts, and robots FPD production equipment, semiconductor devices, electrical and electronic equipment, and loosening prevention

## ● Material/Finish

RoHS

	SWUT
Main Body	FRS-9901 (Equivalent to TW340)
Nylon Ring	Nylon 66

Unit : mm

Part Number	M (Coarse)		B	C (Approx.)	T	Mass (g)
	Nominal of Thread	Pitch				
SWUT-M3	M3	0.5	5.5	6.4	4	0.27
SWUT-M4	M4	0.7	7	8.1	5	0.52
SWUT-M5	M5	0.8	8	9.2	6.5	0.77
SWUT-M6	M6	1	10	11.5	8	1.8
SWUT-M8	M8	1.25	13	15	9.8	3.5
SWUT-M10	M10	1.5	17	19.6	12	7.3

## ● Part number specification

### SWUT-M6

Batch cleanroom packing is provided for orders containing multiple items of the same size.

Individual Sales → P.0000	Cleanroom Wash & Packaging → P.0000	Screw Length Adjustment → P.0000	Vibration Resistant → P.0000	Modification process for captive use → P.0000
1 piece in 1 pack	Cleanroom washed and packed	Not Available	Not Available	Not Available