SAN-B / SANS-B Stopper Screw

SUS Stainless steel



• Part number specification

SAN - M5 - 20 - B Product Code
Type with Hex Socket



- Fine threaded type stopper screw. Fine adjustment is easy.
- For work locating and stopping.
- Round area has already been quenched. It is highly abrasion-resistant.
- All products are provided with lock nut.

| Material/Finish | | | | | |
|-----------------|--|--|--|--|--|
| | SAN-B Made of Steel | SANS-B Made of Stainless Steel | | | |
| Thread Part | S45C Sphere part quenching (hardness: 45 - 50 HRC) Trivalent Chromate Treatment | SUS420J2 Sphere part quenching (hardness: 40 - 50 HRC) | | | |
| Nut | Steel Trivalent Chromate Treatment | Equivalent to SUS304 | | | |

I Init · mm

Dimensions

| Part Number Steel | Part Number Stainless steel | M(Fine) | | s min. | B1 | R | в | с | т | Mass (g) | |
|----------------------|--------------------------------|-------------------|-------|----------|-----|----|----|------|---|------------|--|
| | | Nominal of Thread | Pitch | 5 11111. | ы | ĸ | В | C | | 101033 (g) | |
| SAN-M4-B | SANS-M4-B | M4 | 0.5 | 2.2 | 2 | 4 | 7 | 8.1 | 4 | 2.3 - 3.2 | |
| SAN-M5-B | SANS-M5-B | M5 | 0.5 | 2.8 | 2.5 | 5 | 8 | 9.2 | 4 | 3.1 - 4.6 | |
| SAN-M6-B | SANS-M6-B | M6 | 0.75 | 3 | 3 | 6 | 10 | 11.5 | 4 | 4.5 - 13 | |
| SAN-M8-B | SANS-M8-B | M8 | 0.75 | 4 | 4 | 8 | 13 | 15 | 5 | 9.7 - 23 | |
| SAN-M10-B | SANS-M10-B | M10 | 1 | 5 | 5 | 10 | 17 | 19.6 | 6 | 23 - 35 | |
| SAN-M12-B | SANS-M12-B | M12 | 1 | 6 | 6 | 12 | 19 | 21.9 | 6 | 37 - 68 | |
| SAN-M16-B | SANS-M16-B | M16 | 1.5 | 7 | 8 | 16 | 24 | 27.7 | 8 | 90 - 150 | |

SAN-B Made of Steel SANS-B Made of Stainless Steel

| Part Number | L(mm) 🔁 | | | | | | | | | | |
|-------------|---------|----|----|----|----|----|----|----|-----|--|--|
| | 20 | 25 | 30 | 35 | 40 | 50 | 60 | 80 | 100 | | |
| SAN-M4-B | • | | • | | | | | | | | |
| SAN-M5-B | • | | • | | | | | | | | |
| SAN-M6-B | • | | • | • | • | • | • | | | | |
| SAN-M8-B | | • | • | | • | • | • | | | | |
| SAN-M10-B | | | | | • | • | • | | | | |
| SAN-M12-B | | | | | • | | • | • | | | |
| SAN-M16-B | | | | | | | • | • | • | | |
| SANS-M4-B | • | | • | | | | | | | | |
| SANS-M5-B | • | | • | | | | | | | | |
| SANS-M6-B | • | | • | • | • | • | • | | | | |
| SANS-M8-B | | • | • | | • | • | • | | | | |
| SANS-M10-B | | | | | • | • | • | | | | |
| SANS-M12-B | | | | | • | | • | • | | | |
| SANS-M16-B | | | | | | | • | • | • | | |

 Screw Combination → P.xxxx
 Image: Screw Length Adjustment → P.xxxx

 Please feel free to contact us
 Not Available

 Not Available
 Not Available

