


SSC(INCH) Socket Head Cap Captive Screws (Inch Screws)



SUS Stainless steel






Precautions for Use

- Screw hole inner diameter on the cover side shall be at least the dc dimension.
- The cover thickness should be 0.8 mm or above.
- Installation example

Machine a screw hole on the cover and let through the threaded part of **SSC(INCH)**. Threaded part of **SSC(INCH)** is still engaged with the screw hole on the cover even after the screw is removed from the frame, so **SSC(INCH)** never fall out of the cover.





- It prevents fall-off and loss of the screw. For fixing of protection cover and cover for inspection that are frequently mounted and removed.
- Inch screw type.
- For CE marking. → P.xxxx
- Use a dedicated wrench **SKH(INCH)** for mounting and removal. → P.xxxx
- We also produce captive screws of special specifications, e.g. dimensions, shapes, materials and surface treatment. Please feel free to contact our customer service.



Application

Fixing of protection cover and cover for inspection / CE marking Machine tool / Food machinery / and Electronic device

Material/Finish



	SSC (INCH)
Main body	Equivalent to SUS304
Strength Class	A2-50

Unit:inch

Part Number 1	#Nominal of Thread	L 12								Lm (mm)	D1	L1	В	dc(mm)	Mass(g)
SSC-#4-40	No.4-40UNC	5 / 16	3/8	1/2	5/8					4	0.183	0.112	3/32	1.9	0.63 - 0.9
SSC-#6-32	No.6-32UNC		3/8	1/2	5/8	3/4				5	0.226	0.138	7/64	2.4	1.2 - 1.7
SSC-#8-32	No.8-32UNC		3/8	1/2	5/8	3/4				5	0.27	0.164	9/64	3	1.8 - 2.7
SSC-#10-32	No.10-32UNF		3/8	1/2	5/8	3/4	7/8			6	0.312	0.19	5/32	3.7	2.7 - 4.2
SSC-1 / 4-20	1/4-20UNC				5/8	3/4	7/8	1	1 - 1/4	9	0.375	0.25	3 / 16	4.6	6.2 - 9.3

• Part number specification



