e-nedzi.com

SPE-T Plastic Screw - Hex Socket Set Screws - PEEK

Heat-resistance Chemical-proof



| Material/Finish |
|-------------------------------------|
|-------------------------------------|

🚺 RoHS

| | - 10 |
|-------------------------------|------------------|
| | SPE-T |
| Main body | PEEK/Light brown |
| Heat Resistance Temperature*1 | 260°C |

*1: This is the value for the plastic material. The maximum operating temperature of the product changes with performance conditions such as tightening torque.

A Precautions for Use

Because a cumulative pitch difference is created when PEEK screws are manufactured, use these screws with nuts. If a nut is not used, use a 20 mm or less fit with female thread.



- PEEK is a thermoplastic super-engineering plastic with excellent physical and chemical properties.
- These screws have excellent chemical resistance. They are mostly unaffected by chemicals excluding concentrate sulfuric acid, concentrate nitric acid, and concentrate hydrofluoric acid.
- These screws have excellent heat resistance, water resistance, and high heat resistance strength.
- These screws have excellent abrasion, shock, and fatigue resistance.
- They have high incombustibility that meets V-0 of UL 94.
- The properties and precautions of plastic screws
 - ➡ P.xxxx
- Application

FPD production equipment, semiconductor devices, printed circuit board etching devices, metallic surface treatment equipment and facilities, chemical plants, transformers, electrical and electronic equipment, hot water pumps, and chemical pumps

| | | | | | | | | | | | | | | | | | Unit : mm |
|-------------|---------------------|-------|---|---|---|---|----|----|----|----|----|----|-----|-----|-----------------|-------------|-----------|
| | M (Coarse) | | | | | | | | | | | | | | Torsional*1 | | Qty |
| Part Number | Nominal of Thread ٵ | Pitch | L | 2 | | | | | | | | | В | t | Torque (N∙m) | Mass (g) | per pack |
| SPE-M3-T | M3 | 0.5 | 4 | 5 | 6 | 8 | 10 | 12 | 15 | | | | 1.5 | 2 | 0.21 | 0.023 - 0.1 | 10 |
| SPE-M4-T | M4 | 0.7 | | 5 | 6 | 8 | 10 | 12 | 15 | 20 | | | 2 | 2.5 | 0.47 | 0.05 - 0.25 | 10 |
| SPE-M5-T | M5 | 0.8 | | 5 | 6 | 8 | 10 | 12 | 15 | 20 | | | 2.5 | 3 | 0.96 | 0.05 - 0.37 | 10 |
| SPE-M6-T | M6 | 1 | | | 6 | 8 | 10 | 12 | 15 | 20 | 25 | | 3 | 3.5 | 1.64 | 0.13 - 0.68 | 5 |
| SPE-M8-T | M8 | 1.25 | | | | | 10 | 12 | 15 | 20 | 25 | 30 | 4 | 5 | 3.68 | 0.42 - 1.5 | 5 |

*1: Values in chart are for reference only. They are not guaranteed values. The recommendation torque is 50% of the torsional torque.
When purchasing less volume than one full bag, a separate handling fee is charged. For details, see the Sold Separately Service.

• Related Products

SPE-N Plastic Hexagon Nut (PEEK) is available. → P.xxxx



• Part number specification



🔟 Individual Sales → Pxxxxx 📢 Cleanroom Wash & Packaging → Pxxxx 👹 Srew Length Adjustment → Pxxxx 🛀 Wibration Resistant → Pxxxx 🛀 Modification process for captive use → Pxxxx Available / Add'l charge Available / Add'l charge Available / Add'l charge Not Available Not Available

