






With pilot hole and grip mounting hole





HAK-N With pilot hole and without grip mounting hole




With pilot hole and finger hole











HAK-R With reamer bore and grip mounting hole

HAK-R-N With reamer bore and without grip mounting hole

HAK-R-FH

With reamer bore and finger hole






HAK With pilot hole and grip mounting hole HAK-N With pilot hole and without grip mounting hole

	0 1	•				0 1	U					Unit: mm
Part Number	M (Coarse)		D	Part Number	D 41	ш	Α		ч	<u></u>	Lc	Mass (g)
With grip mounting holes	Nominal of Thread	Pitch	Г	Without grip mounting holes		"	^	5	u	C	LC	Mass (g)
HAK-40	M6	1	14.5	HAK-40-N	40	25	12	13	22	5	15	50
HAK-50	M6	1	17	HAK-50-N	50	28	13	15	27	5	15	87
HAK-63	M6	1	23	HAK-63-N	63	32	14	18	35	5	15	161
HAK-80	M6	1	30	HAK-80-N	80	40	15	25	45	5	15	299

HAK-R With reamer bore and gr	rin mounting hala WAK R N	NA/ith reamor hare and will	haut aria mauntina hala
vvilli reallier bore and gr	ID MOUNTING HOLE ##/#WORK	ii vviilii realliel bore aliu wii	HOUL SHO HIGHHIRE HOLE

Part Number	M (Coarse)		В	Part Number	D 411 H		н А	s	d	R 4 2	1 -	£	M (Coarse)		Mass (g)
With grip mounting holes	Nominal of Thread	Pitch	r	Without grip mounting holes	D I	П	A	5	u	K Z	LI	'	Nominal of Thread	Pitch	iviass (g)
HAK-40-R8	M6	1	14.5	HAK-40-R8-N	40	25	12	13	22	8	15	6.5	M5	8.0	45
HAK-50-R10	M6	1	17	HAK-50-R10-N	50	28	13	15	27	10	18	7.5	M5	0.8	77
HAK-63-R12	M6	1	23	HAK-63-R12-N	63	32	14	18	35	12	22	9	M5	8.0	146
HAK-80-R16	M6	1	30	HAK-80-R16-N	80	40	15	25	45	16	28	12.5	M6	1	264

*1: Hex socket set screw is provided.



• Mini handwheel made of aluminum alloy

• Bore type and with / without grip mounting hole and finger hole can be selected by a product code.

Product Code 13	Bore Type	Grip Mounting Hole	Finger Hole
HAK	Pilot Hole	Yes	No
HAK-N	Pilot Hole	No	No
HAK-FH	Pilot Hole	No	Yes
HAK-R	Reamer Bore	Yes	No
HAK-R-N	Reamer Bore	No	No
HAK-R-FH	Reamer Bore	No	Yes

- There are two color variations. They can be selected by the end symbol of the part number. < No end symbol——Black End Symbol **SG**—Silver gray
- There is no grip supplied with this product. Order a grip separately. → P.xxxx

Material	l/Finisl

• Material init	""	♥ RoHS
	HAK	
Main body	A5056 Anodized (Various Color)	

• Part number specification



HAK-SG

						(If the bore type is for reamer bore)
Product	41	■ 3	■ 2	3	4	

HAK-FH With pilot hole / finger hole

										Unit: mn
Part Number With finger hole	D 1	Н	Α	s	d	С	Lc	P	C1	Mass (g)
HAK-40-FH	40	25	12	13	22	5	15	10.5	14	49
HAK-50-FH	50	28	13	15	27	5	15	15	14	86
HAK-63-FH	63	32	14	18	35	5	15	21	14	159

HAK-R-FH With reamer bore / finger hole

Part Number	D 41	н	^		٦	D 412	1.	M1 (Coarse)		£	В	C ₁	Mass (g)	
With finger hole		П	А	5	a	R 2	Li	Nominal of Thread	Pitch	'	r	Ci	iviass (g)	
HAK-40-R8-FH	40	25	12	13	22	8	15	M5	0.8	6.5	10.5	14	44	
HAK-50-R10-FH	50	28	13	15	27	10	18	M5	0.8	7.5	15	14	76	
HAK-63-R12-FH	63	32	14	18	35	12	22	M5	0.8	9	21	14	144	

*1: Hex socket set screw is provided.