



Material/Finish

 Material/Finish 	🗭 Ro	HS
	KDMS-SC	
Knob	Nylon 6 (Various Color)	
Thread Part	SUSXM7	

- Captive type dimple knob. Prevents fall-off and loss of the knob.
- Foreign matter entry countermeasures in food processing machinery and so on, as well as CE marking support (\rightarrow P.xxxx).
- Dimple on the outer circumference enhances the operability.
- Knob colors can be selected by the end symbol of the part number. White is ideal for products like medical devices.

End Symbol 毛	Knob Color
ВК	Matte Black
WH	Matte White

• Installation example

Make a screw hole in the cover, then pass the knob thread through it. Even when the screw is removed from the frame, the knob does not fall out from the cover because the knob thread catches on the screw hole of the cover.





MAN&MACHINE®

Precautions for Use

- Screw hole inner diameter on the cover side shall be at least d1.
- The cover thickness should be 0.8 mm or above.

Dimensions								Unit : mm	
Part Number 📶 🛛 D	D	M (Coarse)		Lm			-	al.	
		Nominal of Thread	Pitch	Lm	Н	S	d	dı	Mass (g)
KDMS-16-M4-SC	16	M4	0.7	5	11	2	11	3	3-4
KDMS-20-M5-SC	20	M5	0.8	6	14	4	15	3.9	6-7
KDMS-25-M6-SC	25	M6	1	8	18	6	19	4.6	11 - 12
KDMS-32-M8-SC	32	M8	1.25	10	18	6	24	6.3	22 - 23

Part Number	L (mm) 🔁					
	10	16	20	25		
KDMS-16-M4-SC	•	•				
KDMS-20-M5-SC	•	•	•			
KDMS-25-M6-SC		•	•	•		
KDMS-32-M8-SC			•	•		

• Part number specification



For 4 screw length L, select from the sizes marked with lacksquare in the table.

🐂 Cleanroom Wash & Packaging 🔶 P.xxxx 🌾 Screw Combination 🄶 P.xxxx 👘 Screw Length Adjustment 🔶 P.xxxx 🥌 Vibration Resistant 🔶 P.xxxx Available / Add'l charge Not Available Not Available Not Available Available / Add'l charge

NBK

NBK