


SET/SETS Hexalobular Socket Head Cap Screws with Extreme Low Profile

SUS Stainless steel  Protrusion

e-nedzi.com®



● Application

Reducing the size of equipment and devices

● Material/Finish

 RoHS

	SET-NI	SET-BNI	SETS
Main Body	SWCH Nickel Plating	SWCH Black Nickel Plating	SUSXM7 (Equivalent to SUS304)



- Hexalobular socket*1 head cap screws with ultra-thin head.
- For space-saving of equipment/devices and applications with limited overhead space.
- Hexalobular socket shapes*1 are designed to withstand high tightening torque. ➡ P.xxxx
- Install and remove with **SKX** Dedicated Wrench or **SKXB** Dedicated Bit and **SRD** Dedicated Magnetic Screwdriver together.
- Use the **SKX-N** hexalobular wrench for extremely limited access spaces for mounting and removing in tight spaces.
- Also, products with special specifications such as ventilation holes, dimensions, shapes, materials, surface treatments, cleanroom washing & packaging are available. ➡ P.xxxx



* 1 : The hexalobular shape is prescribed by JIS B 1015: 2008(ISO 10664: 2005)"Hexalobular internal driving feature for bolts and screws".

SET-NI Steel - Nickel Plating



Unit : mm

Part Number	M (Coarse)		L 					D1	L1	Applicable wrench	Hexalobular Socket No.	t	Max. Torque (N・m)	Mass (g)	Qty per pack
	Nominal of Thread 	Pitch													
SET-M3-NI	M3	0.5	6	8	10			7	0.8	SKX-6	6	0.75	0.7	0.39 - 0.56	20
SET-M4-NI	M4	0.7	6	8	10	12	16	8	0.9	SKX-8	8	0.9	2.3	0.65 - 1.4	20
SET-M5-NI	M5	0.8		8	10	12	16	9	1	SKX-10	10	1	4	0.73 - 1.7	20

- When purchasing less volume than one full bag, a separate handling fee is charged. For details, see the Sold Separately Service.

SET-BNI Steel - Black Nickel Plating



Unit : mm

Part Number	M (Coarse)		L 					D1	L1	Applicable wrench	Hexalobular Socket No.	t	Max. Torque (N・m)	Mass (g)	Qty per pack
	Nominal of Thread 	Pitch													
SET-M3-BNI	M3	0.5	6	8	10			7	0.8	SKX-6	6	0.75	0.7	0.39 - 0.56	20
SET-M4-BNI	M4	0.7	6	8	10			8	0.9	SKX-8	8	0.9	2.3	0.65 - 0.95	20
SET-M5-BNI	M5	0.8		8	10	12	16	9	1	SKX-10	10	1	4	0.73 - 1.7	20






- When purchasing less volume than one full bag, a separate handling fee is charged. For details, see the Sold Separately Service.

SETS Stainless Steel

Unit : mm

Part Number	M (Coarse)		L 										D1	L1	Applicable wrench	Hexalobular Socket No.	t	Max. Torque (N・m)	Mass (g)	Qty per pack		
	Nominal of Thread 	Pitch																				
SETS-M2	M2	0.4	4	5	6	8	10	12					4 ⁰ _{-0.4}	0.5	SKX-4	4	0.4	0.15	0.047 - 0.23	20		
SETS-M2.6	M2.6	0.45	4	5	6	8	10	12					6 ⁰ _{-0.5}	0.6	SKX-5	5	0.5	0.3	0.17 - 0.41	20		
SETS-M3	M3	0.5			6	8	10	12	16				7 ⁰ _{-0.5}	0.8	SKX-6	6	0.75	0.6	0.39 - 0.84	20		
SETS-M4	M4	0.7			6	8	10	12	16	20	25		8 ⁰ _{-0.5}	0.9	SKX-8	8	0.9	1.5	0.65 - 2.3	20		
SETS-M5	M5	0.8				8	10	12	16	20	25	30		9 ⁰ _{-0.5}	1	SKX-10	10	1	3.1	0.73 - 3.8	20	
SETS-M6	M6	1				8	10	12	16	20	25	30	35	40	12 ⁰ _{-0.6}	1.2	SKX-20	20	1.2	5.3	1.7 - 8.4	20

- When purchasing less volume than one full bag, a separate handling fee is charged. For details, see the Sold Separately Service.

 Individual Sales ➡ P.xxxx	 Cleanroom Wash & Packaging ➡ P.xxxx	 Screw Length Adjustment ➡ P.xxxx	 Vibration Resistant ➡ P.xxxx	 Modification process for captive use ➡ P.xxxx
Available / Add'l charge	Available / Add'l charge	Available / Add'l charge	Available / Add'l charge	Please feel free to contact us

NBK

 ▶ <https://www.nbk1560.com>



● Related Products

SKX Hexalobular Wrench



SKX-N Hexalobular Wrench for Extremely Limited Access Spaces



SKXB Hexalobular Short Bit



SRD Magnet Screwdriver



- Part number specification

SET-M3-8-NI


NBK

 ▶ <https://www.nbk1560.com>