

**SNZF-TBZ**

- Miniature screws for precision instruments.(JCIS 10 - 70)
- M1.4 - M2.6.
- More compact head than standard flat head machine screws.
- Application

Reducing the size of equipment and devices
Compact precision instruments

- Material/Finish



	SNZF-TBZ	SNZFS
Main	SWCH16A	SUSXM7
Body	Black Trivalent Chromate Treatment	(Equivalent to SUS304)

SNZF-TBZ Steel - Black Trivalent Chromate Treatment		SNZFS Stainless steel		Common dimensions											Cross-recessed Socket Number	Qty per Pack
Part Number	Mass (g)	Part Number	Mass (g)	M (Coarse)		L*1						D1	L1			
				Nominal of Thread	Pitch	2	3	4	5	6	8					10
SNZF-M1.4-TBZ	0.016 - 0.066	SNZFS-M1.4	0.016 - 0.066	M1.4	0.3	2	3	4	5	6	8	2	0.45	0	50	
		SNZFS-M1.6	0.033 - 0.11	M1.6	0.35		3	4	5	6	8	10	2.3	0.5	0	50
SNZF-M1.7-TBZ	0.027 - 0.13	SNZFS-M1.7	0.04 - 0.13	M1.7	0.35	2	3	4	5	6	8	10	2.5	0.5	0	50
SNZF-M2-TBZ	0.038 - 0.18	SNZFS-M2	0.056 - 0.18	M2	0.4	2	3	4	5	6	8	10	3	0.6	0	50
SNZF-M2.6-TBZ	0.1 - 0.27	SNZFS-M2.6	0.1 - 0.27	M2.6	0.45		3	4	5	6	8	4	0.8	0		50

*1: SNZFS-M1.7-2-TBZ, SNZFS-M2-2-TBZ are not among the standard products.

- When purchasing less volume than one full bag, a separate handling fee is charged. For details, see the Sold Separately Service.

- Part number specification

SNZFS-M1.7-3

1 2

Individual Sales → P.0000	Cleanroom Wash & Packaging → P.0000	Screw Length Adjustment → P.0000	Vibration Resistant → P.0000	Modification process for captive use → P.0000
Available / Add'l charge	Available / Add'l charge	Not Available	Available / Add'l charge	Not Available