e-nedzi.com

SPA-HA Plastic Screws - Hex Posts - RENY

High strength





RoHS

• Material/Finish

	SPA-HA
Main Body	RENY*1 (50% Glass Fiber Reinforced Polyamide MXD6) (Black)
Heat Resistance Temperature*2	105°C

- *1: RENY is a registered trademark of Mitsubishi Engineering-Plastics Corporation.
- *2: This is the value for the resin material. The operating temperature of the product changes with performance conditions such as tightening torque.



- RENY is a thermoplastic engineering plastic with excellent tensile and bending strength.
- It is highly fatigue-resistant and has excellent creep and heat insulation properties.
- While it is nearly as strong as metal, its weight is approximately 1/5 of iron.
- The properties and precautions of plastic screws

 → P.xxxx

Application

Heat insulation and dew condensation prevention of electric and electronic devices and refrigerating and freezing facilities / Weight saving of offshore instruments, plating facilities, automobiles, airplanes, aerospace devices, etc.

Part Number	M (Coarse)		L 1	4 2			в	14	Mass (g)	Qty	
	Nominal of Thread 1	Pitch					Ь	-	Mass (g)	per Pack	
SPA-M3-HA	M3	0.5	8	10	15	20	5.5	6	0.31 - 0.83	10	
SPA-M4-HA	M4	0.7	8	10	15	20	6	6	0.49 - 1.3	10	

• When purchasing less volume than one full bag, a separate handling fee is charged. For details, see the Sold Separately Service.

• Part number specification



 Individual Sales → Pxxxx
 S Cleanroom Wash & Packaging → Pxxxx
 Image: Serve Length Adjustment →

