



Material/Finish



	SCS-FB Made of Steel	SCSS-FB Made of Stainless Steel
Thread Part	SCM435 Ferroferric Oxide Film (Black)	SUSXM7
Ball	SUJ2 (hardness: 55 - 60 HRC) Ferroferric Oxide Film (Black)	SUS440C (hardness: 55 - 60 HRC) Temper Color (Brown)

Part number specification

SCS-M6-25-FB



										Unit : mm
Part Number Steel	Part Number Stainless steel	M (Coarse)		L	D	d	B	Mass (g)		
		Nominal of Thread	Pitch							
SCS-M4-6-FB	SCSS-M4-6-FB	M4	0.7	6	2.5	2	2	0.4		
SCS-M4-10-FB	SCSS-M4-10-FB	M4	0.7	10	2.5	2	2	0.7		
SCS-M4-16-FB	SCSS-M4-16-FB	M4	0.7	16	2.5	2	2	1		
SCS-M5-8-FB	SCSS-M5-8-FB	M5	0.8	8	3	2.5	2.5	0.8		
SCS-M5-12-FB	SCSS-M5-12-FB	M5	0.8	12	3	2.5	2.5	1.3		
SCS-M5-20-FB	SCSS-M5-20-FB	M5	0.8	20	3	2.5	2.5	2.3		
SCS-M6-10-FB	SCSS-M6-10-FB	M6	1	10	4	3.2	3	1.5		
SCS-M6-16-FB	SCSS-M6-16-FB	M6	1	16	4	3.2	3	2.5		
SCS-M6-20-FB	SCSS-M6-20-FB	M6	1	20	4	3.2	3	3.4		
SCS-M6-25-FB	SCSS-M6-25-FB	M6	1	25	4	3.2	3	4		
SCS-M8-10-FB	SCSS-M8-10-FB	M8	1.25	10	5.5	4.5	4	2.5		
SCS-M8-12-FB	SCSS-M8-12-FB	M8	1.25	12	5.5	4.5	4	3.2		
SCS-M8-20-FB	SCSS-M8-20-FB	M8	1.25	20	5.5	4.5	4	5.7		
SCS-M8-25-FB	SCSS-M8-25-FB	M8	1.25	25	5.5	4.5	4	7.7		
SCS-M8-30-FB	SCSS-M8-30-FB	M8	1.25	30	5.5	4.5	4	9		
SCS-M10-12-FB	SCSS-M10-12-FB	M10	1.5	12	7	6	5	5		
SCS-M10-16-FB	SCSS-M10-16-FB	M10	1.5	16	7	6	5	7		
SCS-M10-20-FB	SCSS-M10-20-FB	M10	1.5	20	7	6	5	9.5		
SCS-M10-25-FB	SCSS-M10-25-FB	M10	1.5	25	7	6	5	11		
SCS-M10-35-FB	SCSS-M10-35-FB	M10	1.5	35	7	6	5	16		
SCS-M12-16-FB	SCSS-M12-16-FB	M12	1.75	16	8.5	7.2	6	10		
SCS-M12-20-FB	SCSS-M12-20-FB	M12	1.75	20	8.5	7.2	6	12.5		
SCS-M12-30-FB	SCSS-M12-30-FB	M12	1.75	30	8.5	7.2	6	20		
SCS-M12-40-FB	SCSS-M12-40-FB	M12	1.75	40	8.5	7.2	6	28		
SCS-M16-20-FB	SCSS-M16-20-FB	M16	2	20	12	10.7	8	22		
SCS-M16-25-FB	SCSS-M16-25-FB	M16	2	25	12	10.7	8	28		
SCS-M16-35-FB	SCSS-M16-35-FB	M16	2	35	12	10.7	8	41		
SCS-M16-50-FB	SCSS-M16-50-FB	M16	2	50	12	10.7	8	48		

*: **SCS-M8-10-FB** **SCS-M10-12-FB** **SCS-M12-16-FB** **SCS-M16-20-FB** **SCSS-M8-10-FB** **SCSS-M10-12-FB** **SCSS-M12-16-FB** **SCSS-M16-20-FB**
has a shallow Hex Socket hole depth.

Cleanroom Wash & Packaging → P.xxxx	Screw Combination → P.xxxx	Screw Length Adjustment → P.xxxx	Vibration Resistant → P.xxxx
Please feel free to contact us	Available / Add'l charge	Not Available	Available / Add'l charge