


SCX-N Hex Nuts - Ceramic



Heat-resistance Chemical-proof Electrical Insulation



- Ceramic made from 99.5% high-purity alumina.
- Usable continually at 1500°C.
- They have excellent heat resistance, chemical resistance, and electrical insulation.
- The properties of ceramic screws → P.xxxx
- Application

FPD production equipment, semiconductor devices, printed circuit board etching devices, metallic surface treatment equipment and facilities, and chemical plants

Material/Finish



	SCX-N
Main Body	Al ₂ O ₃ (99.5% Alumina)

SCX-N Hex Nuts

Unit : mm

Part Number	M (Coarse)		B	T	Mass (g)
	Nominal of Thread	Pitch			
SCX-M3-N	M3	0.5	5.5	2.3	0.16
SCX-M4-N	M4	0.7	7	3.1	0.38
SCX-M5-N	M5	0.8	8	4.6	0.68
SCX-M6-N	M6	1	10	5	1.2
SCX-M8-N	M8	1.25	13	6.7	2.8
SCX-M10-N	M10	1.5	16	8.2	5.1

- Part number specification

SCX-M5-N



Individual Sales → P.xxxx	Cleanroom Wash & Packaging → P.xxxx	Screw Length Adjustment → P.xxxx	Vibration Resistant → P.xxxx	Modification process for captive use → P.xxxx
1 piece in 1 pack	Available / Add'l charge	Not Available	Not Available	Not Available