

- The ventilation hole easily releases gas trapped in the screw holes of equipment and machines, and supports vacuum drawing of vacuum devices.
- Cleanroom wash and cleanroom packing are completed.

• Application

Vacuum device / Vacuum container / FPD production device / Semiconductor manufacturing device / Electron microscope

• Material/Finish



	SVPS
Main body	SUSXM7 (Equivalent to SUS304)


Unit : mm

Part Number 1	M (Coarse)		L 2								D1	L1	d max.	Cross-recessed Socket Number	Mass (g)	Qty per pack
	Nominal of Thread	Pitch														
SVPS-M3	M3	0.5	8	10	12	16					5.5	2	1.2	2	0.61 - 0.94	10
SVPS-M4	M4	0.7		10	12	16	20				7	2.6	1.5	2	1.3 - 2.1	10
SVPS-M5	M5	0.8			12	16	20	25			9	3.3	1.5	2	2.7 - 4.2	10
SVPS-M6	M6	1			12	16	20	25	30		10.5	3.9	2	3	4.3 - 7.4	10
SVPS-M8	M8	1.25					20	25	30	35	14	5.2	2	3	11 - 16	10

- When purchasing less volume than one full bag, a separate handling fee is charged. For details, see the Sold Separately Service.

• Related Products


For ventilation of drilled hole, please use **SWAS-VF**.



SWAS-VF Washer
(with Ventilation Groove)

• Part number specification

SVPS-M4-12



1 Individual Sales	Cleanroom Wash & Packaging	Screw Length Adjustment	Vibration Resistant	Modification process for captive use
Available / Add'l charge	Cleanroom washed and packed	Available / Add'l charge	Not Available	Please feel free to contact us