

- Cleanroom wash and cleanroom packing are completed.
- Combine this item with **SVST** Socket Head Cap Screws with Ventilation Hole-titanium().
- Application

Vacuum devices, vacuum chambers, FPD production equipment, semiconductor devices, and electron microscopes

| Material/Finish | 🚺 Rohs |
|-------------------------------------|---------------------------|
| | SWAT-VF |
| Main Body | TP340C (Grade 2 Titanium) |

| | | | | | Unit : mm |
|---------------|---------|-----|----|-----|-----------|
| Part Number ៕ | Nominal | d | D | t | Mass (g) |
| SWAT-3-VF | 3 | 3.2 | 7 | 0.5 | 0.068 |
| SWAT-4-VF | 4 | 4.3 | 9 | 0.8 | 0.18 |
| SWAT-5-VF | 5 | 5.3 | 10 | 1 | 0.25 |

• Usage example

Gas trapped at the bottom of a screw hole is released through **SWAT-VF** , and gas trapped in a drilled hole is released through **SVST** ().

SWAT-VF Titanium Washer with Ventilation Grooves



Part number specification

Batch cleanroom packing is provided for orders containing multiple items of the same size.

| Individual Sales | < Cleanroom Wash & Packaging | Screw Length Adjustment | 🕋 Vibration Resistant | Modification process for captive use |
|--------------------------------------|------------------------------|-------------------------|-----------------------|--------------------------------------|
| 1 piece in 1 pack | Cleanroom washed and packed | Not Available | Not Available | Not Available |