

## ● 材质、表面处理



|    | HNBRs  |
|----|--------|
| 主体 | SUS304 |



- 用于调整铰链和安装面之间的间隙的辅助垫片。
- 不锈钢制。
- 与不锈钢制大型滑动铰链 **HNNVS** **HNNMS** **HNNHS** 及金属铰链组合使用。

单位: mm


| 型号              | L <sub>2</sub> | s   | B <sub>1</sub> | B <sub>2</sub> | d | L <sub>1</sub> *1 | P <sub>1</sub> *1 | P <sub>2</sub> | 质量 (g) |
|-----------------|----------------|-----|----------------|----------------|---|-------------------|-------------------|----------------|--------|
| HNBRs-30-1-MT   | 30             | 1   | 10.8           | 6              | 4 | 30                | 18                | 18             | 2.2    |
| HNBRs-30-1.5-MT | 30             | 1.5 | 10.8           | 6              | 4 | 30                | 18                | 18             | 3.3    |
| HNBRs-30-3-MT   | 30             | 3   | 10.8           | 6              | 4 | 30                | 18                | 18             | 6.4    |
| HNBRs-30-5-MT   | 30             | 5   | 10.8           | 6              | 4 | 30                | 18                | 18             | 10.5   |
| HNBRs-40-1-MT   | 40             | 1   | 14.5           | 7.5            | 5 | 40                | 25                | 25             | 4.1    |
| HNBRs-40-1.5-MT | 40             | 1.5 | 14.5           | 7.5            | 5 | 40                | 25                | 25             | 6.1    |
| HNBRs-40-3-MT   | 40             | 3   | 14.5           | 7.5            | 5 | 40                | 25                | 25             | 12.1   |
| HNBRs-40-5-MT   | 40             | 5   | 14.5           | 7.5            | 5 | 40                | 25                | 25             | 20.1   |
| HNBRs-50-1-MT   | 50             | 1   | 18             | 10             | 6 | 50                | 30                | 30             | 6.4    |
| HNBRs-50-1.5-MT | 50             | 1.5 | 18             | 10             | 6 | 50                | 30                | 30             | 10     |
| HNBRs-50-3-MT   | 50             | 3   | 18             | 10             | 6 | 50                | 30                | 30             | 20     |
| HNBRs-50-5-MT   | 50             | 5   | 18             | 10             | 6 | 50                | 30                | 30             | 30.8   |
| HNBRs-60-1-MT   | 60             | 1   | 21.5           | 12.5           | 8 | 60                | 36                | 36             | 9      |
| HNBRs-60-1.5-MT | 60             | 1.5 | 21.5           | 12.5           | 8 | 60                | 36                | 36             | 13.6   |
| HNBRs-60-3-MT   | 60             | 3   | 21.5           | 12.5           | 8 | 60                | 36                | 36             | 27.2   |
| HNBRs-60-5-MT   | 60             | 5   | 21.5           | 12.5           | 8 | 60                | 36                | 36             | 43.6   |

\*1: 请选择安装的铰链尺寸与L<sub>1</sub>及P<sub>1</sub>一致的型号。

## ● 适用铰链

| 型号       | 适用铰链                                                                                                |
|----------|-----------------------------------------------------------------------------------------------------|
| HNBRs-30 | HNG-A / HNGA-A / HNGS-A-NI / HNGS-A-A4                                                              |
| HNBRs-40 | HNG-C / HNGS-C-NI / HNG-A / HNGA-A / HNGS-A-NI / HNGS-A-A4 / HNJ-A / HNJS-A / HNNVS / HNNMS / HNNHS |
| HNBRs-50 | HNG-C / HNGS-C-NI / HNG-A / HNGA-A / HNGS-A-NI / HNGS-A-A4 / HNJ-A / HNJS-A / HNNVS / HNNMS / HNNHS |
| HNBRs-60 | HNG-C / HNGS-C-NI / HNG-A / HNGA-A / HNGS-A-NI / HNGS-A-A4 / HNJ-A / HNJS-A / HNNVS / HNNMS / HNNHS |

## ● 使用例



## ● 型号指定

**HNBRs-30-3-MT**