

- 酚醛树脂制，具有优良的耐久性。
- M4~M10的丰富螺纹尺寸。
- 材质、表面处理



	KKM 外螺纹	KKF 内螺纹
旋钮	酚醛树脂(黑)	酚醛树脂(黑)
螺纹部	钢 三价铬酸盐处理	黄铜 镀镍

尺寸


单位：mm

型号 外螺纹	质量(g)	型号 内螺纹	Lf	质量(g)	D	M(粗牙)		H	s	d
						螺纹公称直径	螺距			
KKM-18-M4	4 - 6	KKF-18-M4	9	4	18	M4	0.7	13	6	10
KKM-20-M5	7 - 9	KKF-20-M5	10	5	20	M5	0.8	14	6	12
KKM-24-M5	9	KKF-24-M5	10	7	24	M5	0.8	16	7	13
KKM-24-M6	12 - 13	KKF-24-M6	10	9	24	M6	1	16	7	13
KKM-30-M6	14 - 17	KKF-30-M6	11	12	30	M6	1	18	7	15
KKM-30-M8	20 - 24	KKF-30-M8	11	13	30	M8	1.25	18	7	15
KKM-35-M8	22 - 25	KKF-35-M8	11	16	35	M8	1.25	19	8	18
KKM-35-M10	35	KKF-35-M10	11	18	35	M10	1.5	19	8	18

型号 外螺纹	Lm(mm)									
	10	12	15	18	20	25	28	30	32	
KKM-18-M4	●		●		●					
KKM-20-M5	●			●		●				
KKM-24-M5	●									
KKM-24-M6					●		●			
KKM-30-M6	●				●		●			
KKM-30-M8						●			●	
KKM-35-M8		●				●				
KKM-35-M10								●		

- 型号指定

KKM-30-M6 - 10



外螺纹型 1 螺纹长度Lm请从表中标有●的尺寸中选择。