



● 材质、表面处理

	KSF	KSFS
旋钮	尼龙6(亚光黑)	尼龙6(亚光黑)
螺纹部	钢 三价铬酸盐处理	SUS303



RoHS

- 七角形是手感舒适的理想外形。
- 备有外螺纹型的七角形旋钮 **KSM** **KSMS** **KSM-PF**。→ P. XXXX
- 可根据产品符号选择螺纹部的材质。

产品符号	螺纹部材质
KSF	钢制
KSFS	不锈钢制

KSF 螺纹部：钢制 **KSFS** 螺纹部：不锈钢制

单位：mm

型号 	型号 	D	M(粗牙)		Lf min.	H	s	d	质量(g)
			螺纹公称直径	螺距					
KSF-25-M4		25	M4	0.7	7.5	16	8	12	5
KSF-25-M5	KSFS-25-M5	25	M5	0.8	9.5	16	8	12	7
KSF-25-M6		25	M6	1	9	16	8	12	7
KSF-32-M4		32	M4	0.7	6.5	20	10	14	11
KSF-32-M5	KSFS-32-M5	32	M5	0.8	9.5	20	10	14	10
KSF-32-M6	KSFS-32-M6	32	M6	1	12	20	10	14	9
KSF-40-M6	KSFS-40-M6	40	M6	1	12	25	13	18	21
KSF-40-M8	KSFS-40-M8	40	M8	1.25	14	25	13	18	19
KSF-40-M10		40	M10	1.5	14	25	13	18	23
KSF-50-M8	KSFS-50-M8	50	M8	1.25	14	32	17	22	41
KSF-50-M10	KSFS-50-M10	50	M10	1.5	18	32	17	22	37
KSF-50-M12		50	M12	1.75	18	32	17	22	35
KSF-63-M10	KSFS-63-M10	63	M10	1.5	18	40	21	26	67
KSF-63-M12	KSFS-63-M12	63	M12	1.75	22	40	21	26	61
KSF-63-M16		63	M16	2	22	40	21	26	71
KSF-80-M12	KSFS-80-M12	80	M12	1.75	22	50	25	35	120
KSF-80-M16	KSFS-80-M16	80	M16	2	30	50	25	35	140

● 型号指定

KSFS-32-M6



 无尘洗净・无尘包装 → P. xxxx	 螺纹组合 → P. xxxx	 螺纹切割 → P. xxxx	 防松动 → P. xxxx	 激光刻印 → P. xxxx
欢迎咨询	可对应, 费用另计	不可对应	不可对应	可对应, 费用另计