


**SHN-LP**

薄形六角螺母

空间



● 材质、表面处理

**SHN-LP**

主体

钢
三价铬酸盐处理

● 符合ISO 4035标准的薄形六角螺母。

● 可节省设备与装置的空间或用于空间有限的部位。

● 用途

设备、装置的省空间化

单位 : mm

型号 	M(粗牙)		B	T	质量(g)	每包数量
	螺纹公称直径	螺距				
SHN-M2-LP	M2	0.4	4	1.2	0.08	50
SHN-M2.5-LP	M2.5	0.45	5	1.6	0.17	50
SHN-M2.6-LP	M2.6	0.45	5	1.6	0.18	10
SHN-M3-LP	M3	0.5	5.5	1.8	0.21	50
SHN-M3.5-LP	M3.5	0.6	6	2	0.27	50
SHN-M4-LP	M4	0.7	7	2.2	0.47	50
SHN-M5-LP	M5	0.8	8	2.7	0.6	50
SHN-M6-LP	M6	1	10	3.2	1.3	50
SHN-M8-LP	M8	1.25	13	4	2.8	50
SHN-M10-LP	M10	1.5	17	5	6.3	20
SHN-M12-LP	M12	1.75	19	6	9.1	20
SHN-M14-LP	M14	2	22	7	13.5	10
SHN-M16-LP	M16	2	24	8	17.2	10

● 数量未满1包的订单，会另外收取手续费。详情请垂询散装零售服务。

● 型号指定

SHN-M5-LP

 散装零售 → P. xxxx
可对应，费用另计

 无尘洗净・无尘包装 → P. xxxx
可对应，费用另计

 螺纹切割 → P. xxxx
不可对应

 防松动 → P. xxxx
不可对应

 防脱落加工 → P. xxxx
不可对应