



- 用于定位的平行销。
- 已变更两端尺寸容许偏差的台阶型。
- 请与定位销用衬套 **PJA** (→ P.xxxx)
PJB (→ P.xxxx) 组合使用。

● 材质、表面处理



	PJP
主体	SUJ2 (硬度58HRC以上)、研磨

单位 : mm

型号	D 1			L 2	L1	L2	质量 (g)
		p ⁶	h ₇				
PJP-3-10	3	+0.012 +0.006	0 -0.010	10	1	7	0.6
PJP-3-15	3	+0.012 +0.006	0 -0.010	15	1	10	0.8
PJP-3-20	3	+0.012 +0.006	0 -0.010	20	1	13	1.1
PJP-4-10	4	+0.020 +0.012	0 -0.012	10	1.5	7	1
PJP-4-15	4	+0.020 +0.012	0 -0.012	15	1.5	10	1.5
PJP-4-20	4	+0.020 +0.012	0 -0.012	20	1.5	13	2
PJP-5-10	5	+0.020 +0.012	0 -0.012	10	1.5	7	1.6
PJP-5-15	5	+0.020 +0.012	0 -0.012	15	1.5	10	2.4
PJP-5-18	5	+0.020 +0.012	0 -0.012	18	1.5	12	2.8
PJP-5-20	5	+0.020 +0.012	0 -0.012	20	1.5	13	3.1
PJP-6-10	6	+0.020 +0.012	0 -0.012	10	1.5	7	2.3
PJP-6-15	6	+0.020 +0.012	0 -0.012	15	1.5	10	3.4
PJP-6-18	6	+0.020 +0.012	0 -0.012	18	1.5	12	4.1
PJP-6-20	6	+0.020 +0.012	0 -0.012	20	1.5	13	4.5
PJP-8-20	8	+0.024 +0.015	0 -0.015	20	2	13	8
PJP-8-25	8	+0.024 +0.015	0 -0.015	25	2	16	10
PJP-8-30	8	+0.024 +0.015	0 -0.015	30	2	19	12
PJP-10-25	10	+0.024 +0.015	0 -0.015	25	2	16	16
PJP-10-30	10	+0.024 +0.015	0 -0.015	30	2	19	19
PJP-12-40	12	+0.029 +0.018	0 -0.018	40	2	25	36

● 型号指定

PJP-5-15

产品
符号 **1** **2**

无尘洗净・无尘包装 → P.xxxx	防松动 → P.xxxx	激光刻印 → P.xxxx
不可对应	不可对应	不可对应