



● 材质、表面处理

|     |                        |
|-----|------------------------|
|     | SCBS-R 不锈钢制            |
| 螺纹部 | 相当于SUS304              |
| 球   | SUS440C (硬度59 - 66HRC) |

● 型号指定

SCBS-M6-20-R



- 通过整球的点接触，牢牢地固定工件。
- 用于刀夹的止动螺丝、压力件或挡块等。
- 也生产螺纹公称直径、螺纹长度与表面处理等特殊规格的产品。请垂询客户中心。

单位：mm

| 型号<br>1<br>不锈钢制 | M(粗牙)  |      | L    | D1  | D     | L1 | B  | 容许载荷<br>(N) | 质量 (g) |
|-----------------|--------|------|------|-----|-------|----|----|-------------|--------|
|                 | 螺纹公称直径 | 螺距   |      |     |       |    |    |             |        |
| SCBS-M4-10-R    | M4     | 0.7  | 10.5 | 7   | 2.5   | 4  | 3  | 2040        | 1.5    |
| SCBS-M4-12-R    | M4     | 0.7  | 12.5 | 7   | 2.5   | 4  | 3  | 2040        | 1.7    |
| SCBS-M4-16-R    | M4     | 0.7  | 16.5 | 7   | 2.5   | 4  | 3  | 2040        | 1.9    |
| SCBS-M4-20-R    | M4     | 0.7  | 20.5 | 7   | 2.5   | 4  | 3  | 2040        | 2.2    |
| SCBS-M4-25-R    | M4     | 0.7  | 25.5 | 7   | 2.5   | 4  | 3  | 2040        | 2.5    |
| SCBS-M5-12-R    | M5     | 0.8  | 12.6 | 8.5 | 3     | 5  | 4  | 3000        | 2.9    |
| SCBS-M5-16-R    | M5     | 0.8  | 16.6 | 8.5 | 3     | 5  | 4  | 3000        | 3.4    |
| SCBS-M5-20-R    | M5     | 0.8  | 20.6 | 8.5 | 3     | 5  | 4  | 3000        | 3.9    |
| SCBS-M5-25-R    | M5     | 0.8  | 25.6 | 8.5 | 3     | 5  | 4  | 3000        | 4.4    |
| SCBS-M5-30-R    | M5     | 0.8  | 30.6 | 8.5 | 3     | 5  | 4  | 3000        | 5      |
| SCBS-M6-16-R    | M6     | 1    | 16.8 | 10  | 4     | 6  | 5  | 4500        | 5.6    |
| SCBS-M6-20-R    | M6     | 1    | 20.8 | 10  | 4     | 6  | 5  | 4500        | 6.5    |
| SCBS-M6-25-R    | M6     | 1    | 25.8 | 10  | 4     | 6  | 5  | 4500        | 7.6    |
| SCBS-M6-30-R    | M6     | 1    | 30.8 | 10  | 4     | 6  | 5  | 4500        | 8.7    |
| SCBS-M6-40-R    | M6     | 1    | 40.8 | 10  | 4     | 6  | 5  | 4500        | 11     |
| SCBS-M8-20-R    | M8     | 1.25 | 21.2 | 13  | 5.56  | 8  | 6  | 9000        | 13.5   |
| SCBS-M8-30-R    | M8     | 1.25 | 31.2 | 13  | 5.56  | 8  | 6  | 9000        | 17.5   |
| SCBS-M8-35-R    | M8     | 1.25 | 36.2 | 13  | 5.56  | 8  | 6  | 9000        | 19     |
| SCBS-M8-40-R    | M8     | 1.25 | 41.2 | 13  | 5.56  | 8  | 6  | 9000        | 21.5   |
| SCBS-M8-50-R    | M8     | 1.25 | 51.2 | 13  | 5.56  | 8  | 6  | 9000        | 25     |
| SCBS-M10-25-R   | M10    | 1.5  | 26.7 | 16  | 7.14  | 10 | 8  | 14400       | 26     |
| SCBS-M10-30-R   | M10    | 1.5  | 31.7 | 16  | 7.14  | 10 | 8  | 14400       | 29     |
| SCBS-M10-40-R   | M10    | 1.5  | 41.7 | 16  | 7.14  | 10 | 8  | 14400       | 34     |
| SCBS-M10-50-R   | M10    | 1.5  | 51.7 | 16  | 7.14  | 10 | 8  | 14400       | 39     |
| SCBS-M10-60-R   | M10    | 1.5  | 61.7 | 16  | 7.14  | 10 | 8  | 14400       | 47     |
| SCBS-M12-30-R   | M12    | 1.75 | 32   | 18  | 7.94  | 12 | 10 | 18000       | 40     |
| SCBS-M12-50-R   | M12    | 1.75 | 52   | 18  | 7.94  | 12 | 10 | 18000       | 56     |
| SCBS-M12-80-R   | M12    | 1.75 | 82   | 18  | 7.94  | 12 | 10 | 18000       | 83     |
| SCBS-M16-40-R   | M16    | 2    | 43.3 | 24  | 11.91 | 16 | 14 | 43800       | 91     |
| SCBS-M16-60-R   | M16    | 2    | 63.3 | 24  | 11.91 | 16 | 14 | 43800       | 122    |
| SCBS-M16-80-R   | M16    | 2    | 83.3 | 24  | 11.91 | 16 | 14 | 43800       | 154    |

无尘洗净・无尘包装 → P. xxxx

欢迎洽询

螺纹组合 → P. xxxx

不可对应

螺纹切割 → P. xxxx

不可对应

防松动 → P. xxxx

可对应, 费用另计