



● 材质、表面处理



	SCS-F 钢制
螺纹部	SCM435 四氧化三铁保护膜(黑)
球	SUJ2(硬度62 - 67HRC)

● 型号指定

SCS-M6-25-F



SCS-F

SCSS-F



- 通过平面头钢球进行面接触。不会损伤工件。
- 球可灵活旋转即使配合面为倾斜面，也能牢牢地夹紧。
- 用于刀夹的止动螺丝、压力件或挡块等。
- 也生产螺纹公称直径、螺纹长度与表面处理等特殊规格的产品。请垂询客户中心。

单位：mm

型号 钢制	M(粗牙) 螺纹公称直径	螺距	L	D	d(参考值)	B	容许载荷 (N)	质量(g)
SCS-M4-6-F	M4	0.7	6	2.5	1.9	2	3500	0.4
SCS-M4-10-F	M4	0.7	10	2.5	1.9	2	3500	0.7
SCS-M4-16-F	M4	0.7	16	2.5	1.9	2	3500	1
SCS-M5-8-F	M5	0.8	8	3	2.4	2.5	5000	0.8
SCS-M5-12-F	M5	0.8	12	3	2.4	2.5	5000	1.3
SCS-M5-20-F	M5	0.8	20	3	2.4	2.5	5000	2.3
SCS-M6-10-F	M6	1	10	4	3.1	3	9000	1.5
SCS-M6-16-F	M6	1	16	4	3.1	3	9000	2.5
SCS-M6-20-F	M6	1	20	4	3.1	3	9000	3.4
SCS-M6-25-F	M6	1	25	4	3.1	3	9000	4
SCS-M8-10-F	M8	1.25	10	5.56	4.4	4	15000	2.5
SCS-M8-12-F	M8	1.25	12	5.56	4.4	4	15000	3.2
SCS-M8-20-F	M8	1.25	20	5.56	4.4	4	15000	5.7
SCS-M8-25-F	M8	1.25	25	5.56	4.4	4	15000	7.7
SCS-M8-30-F	M8	1.25	30	5.56	4.4	4	15000	9
SCS-M10-12-F	M10	1.5	12	7	5.9	5	24000	5
SCS-M10-16-F	M10	1.5	16	7	5.9	5	24000	7
SCS-M10-20-F	M10	1.5	20	7	5.9	5	24000	9.5
SCS-M10-25-F	M10	1.5	25	7	5.9	5	24000	11
SCS-M10-35-F	M10	1.5	35	7	5.9	5	24000	16
SCS-M12-16-F	M12	1.75	16	8.5	7.1	6	30000	10
SCS-M12-20-F	M12	1.75	20	8.5	7.1	6	30000	12.5
SCS-M12-30-F	M12	1.75	30	8.5	7.1	6	30000	20
SCS-M12-40-F	M12	1.75	40	8.5	7.1	6	30000	28
SCS-M16-20-F	M16	2	20	12	10.4	8	73000	22
SCS-M16-25-F	M16	2	25	12	10.4	8	73000	28
SCS-M16-35-F	M16	2	35	12	10.4	8	73000	41
SCS-M16-50-F	M16	2	50	12	10.4	8	73000	48

- SCS-M8-10-F | SCS-M10-12-F | SCS-M12-16-F | SCS-M16-20-F 的内六角孔深度较浅。

无尘洗净・无尘包装 → P. xxxx

欢迎洽询

螺纹组合 → P. xxxx

可对应，费用另计

螺纹切削 → P. xxxx

不可对应

防松动 → P. xxxx

可对应，费用另计