



● 材质、表面处理



	SCSS-F 不锈钢制
螺纹部	相当于SUS304
球	SUS440C (硬度 59 - 66HRC)

● 型号指定

SCSS-M6-25-F



- 通过平面头钢球进行面接触。不会损伤工件。
- 球可灵活旋转即使配合面为倾斜面，也能牢牢地夹紧。
- 用于刀夹的止动螺丝、压力件或挡块等。
- 也生产螺纹公称直径、螺纹长度与表面处理等特殊规格的产品。请垂询客户中心。

单位：mm

型号 1 不锈钢制	M (粗牙)		L	D	d (参考值)	B	容许载荷 (N)	质量 (g)
	螺纹公称直径	螺距						
SCSS-M4-6-F	M4	0.7	6	2.5	1.9	2	2040	0.4
SCSS-M4-10-F	M4	0.7	10	2.5	1.9	2	2040	0.7
SCSS-M4-16-F	M4	0.7	16	2.5	1.9	2	2040	1
SCSS-M5-8-F	M5	0.8	8	3	2.4	2.5	3000	0.8
SCSS-M5-12-F	M5	0.8	12	3	2.4	2.5	3000	1.3
SCSS-M5-20-F	M5	0.8	20	3	2.4	2.5	3000	2.3
SCSS-M6-10-F	M6	1	10	4	3.1	3	4500	1.5
SCSS-M6-16-F	M6	1	16	4	3.1	3	4500	2.5
SCSS-M6-20-F	M6	1	20	4	3.1	3	4500	3.4
SCSS-M6-25-F	M6	1	25	4	3.1	3	4500	4
SCSS-M8-10-F	M8	1.25	10	5.56	4.4	4	9000	2.5
SCSS-M8-12-F	M8	1.25	12	5.56	4.4	4	9000	3.2
SCSS-M8-20-F	M8	1.25	20	5.56	4.4	4	9000	5.7
SCSS-M8-25-F	M8	1.25	25	5.56	4.4	4	9000	7.7
SCSS-M8-30-F	M8	1.25	30	5.56	4.4	4	9000	9
SCSS-M10-12-F	M10	1.5	12	7.14	5.9	5	14400	5
SCSS-M10-16-F	M10	1.5	16	7.14	5.9	5	14400	7
SCSS-M10-20-F	M10	1.5	20	7.14	5.9	5	14400	9.5
SCSS-M10-25-F	M10	1.5	25	7.14	5.9	5	14400	11
SCSS-M10-35-F	M10	1.5	35	7.14	5.9	5	14400	16
SCSS-M12-16-F	M12	1.75	16	7.94	6.7	6	18000	10
SCSS-M12-20-F	M12	1.75	20	7.94	6.7	6	18000	12.5
SCSS-M12-30-F	M12	1.75	30	7.94	6.7	6	18000	20
SCSS-M12-40-F	M12	1.75	40	7.94	6.7	6	18000	28
SCSS-M16-20-F	M16	2	20	11.91	10.4	8	43800	22
SCSS-M16-25-F	M16	2	25	11.91	10.4	8	43800	28
SCSS-M16-35-F	M16	2	35	11.91	10.4	8	43800	41
SCSS-M16-50-F	M16	2	50	11.91	10.4	8	43800	48

- SCSS-M8-10-F SCSS-M10-12-F SCSS-M12-16-F SCSS-M16-20-F 的内六角孔深度较浅。

无尘洗净・无尘包装 → P. xxxx

欢迎洽询

螺纹组合 → P. xxxx

可对应，费用另计

螺纹切削 → P. xxxx

不可对应

防松动 → P. xxxx

可对应，费用另计