



● 材质、表面处理



	SCSS-R 不锈钢制
螺纹部	相当于SUS304
球	SUS440C (硬度59 - 66HRC)

● 型号指定

SCSS-M6-25-R



SCSS-R



SCSS-R

- 通过整球的点接触，牢牢地固定工件。
- 用于刀夹的止动螺丝、压力件或挡块等。
- 也生产螺纹公称直径、螺纹长度与表面处理等特殊规格的产品。请垂询客户中心。

单位：mm

型号 1 不锈钢制	M(粗牙)		L	D	B	容许载荷(N)	质量(g)
	螺纹公称直径	螺距					
SCSS-M3-5-R	M3	0.5	5.2	1.5	1.5	1620	0.3
SCSS-M3-10-R	M3	0.5	10.2	1.5	1.5	1620	0.6
SCSS-M4-6-R	M4	0.7	6.5	2.5	2	2040	0.4
SCSS-M4-10-R	M4	0.7	10.5	2.5	2	2040	0.7
SCSS-M4-16-R	M4	0.7	16.5	2.5	2	2040	1
SCSS-M5-8-R	M5	0.8	8.6	3	2.5	3000	0.8
SCSS-M5-12-R	M5	0.8	12.6	3	2.5	3000	1.3
SCSS-M5-20-R	M5	0.8	20.6	3	2.5	3000	2.3
SCSS-M6-10-R	M6	1	10.8	4	3	4500	1.5
SCSS-M6-16-R	M6	1	16.8	4	3	4500	2.5
SCSS-M6-20-R	M6	1	20.8	4	3	4500	3.4
SCSS-M6-25-R	M6	1	25.8	4	3	4500	4
SCSS-M8-10-R	M8	1.25	11.2	5.56	4	9000	2.5
SCSS-M8-12-R	M8	1.25	13.2	5.56	4	9000	3.2
SCSS-M8-20-R	M8	1.25	21.2	5.56	4	9000	5.7
SCSS-M8-25-R	M8	1.25	26.2	5.56	4	9000	7.7
SCSS-M8-30-R	M8	1.25	31.2	5.56	4	9000	9
SCSS-M10-12-R	M10	1.5	13.7	7.14	5	14400	5
SCSS-M10-16-R	M10	1.5	17.7	7.14	5	14400	7
SCSS-M10-20-R	M10	1.5	21.7	7.14	5	14400	9.5
SCSS-M10-25-R	M10	1.5	26.7	7.14	5	14400	11
SCSS-M10-35-R	M10	1.5	36.7	7.14	5	14400	16
SCSS-M12-16-R	M12	1.75	18	7.94	6	18000	10
SCSS-M12-20-R	M12	1.75	22	7.94	6	18000	12.5
SCSS-M12-30-R	M12	1.75	32	7.94	6	18000	20
SCSS-M12-40-R	M12	1.75	42	7.94	6	18000	28
SCSS-M16-20-R	M16	2	23.3	11.91	8	43800	22
SCSS-M16-25-R	M16	2	28.3	11.91	8	43800	28
SCSS-M16-35-R	M16	2	38.3	11.91	8	43800	41
SCSS-M16-50-R	M16	2	53.3	11.91	8	43800	48

- SCSS-M8-10-R | SCSS-M10-12-R | SCSS-M12-16-R | SCSS-M16-20-R 的内六角孔深度较浅。

 无尘洗净・无尘包装 → P. xxxx

欢迎洽询

 螺纹组合 → P. xxxx

可对应，费用另计

 螺纹切削 → P. xxxx

不可对应

 防松动 → P. xxxx

可对应，费用另计