


SWA-AW 调节垫圈(钢制、四氧化三铁保护膜)



\*D=20以下: C0.2以下  
D=20以上: C0.5以下

● 材质、表面处理



|    | SWA-AW                 |
|----|------------------------|
| 主体 | 相当于S45C<br>四氧化三铁保护膜(黑) |



- 外径和厚度的规格比一般的平垫圈更丰富。
- 用于确保长孔部位的座面以及与铝、树脂等临界座面压力较低的材料连接。
- 用于调节安装时的累积误差。

● 用途

高度调整・防止座面凹陷

单位: mm

| 型号          | d | D  | t |     |   |   |   | 质量(g)       | 每包数量 |
|-------------|---|----|---|-----|---|---|---|-------------|------|
|             |   |    | 1 | 1.5 | 2 | 3 | 5 |             |      |
| SWA-2-8-AW  | 2 | 8  | ● |     | ● |   |   | 0.38 - 0.75 | 10   |
| SWA-3-8-AW  | 3 | 8  | ● |     | ● |   |   | 0.35 - 0.69 | 10   |
| SWA-3-10-AW | 3 | 10 | ● |     | ● |   |   | 0.56 - 1.1  | 10   |
| SWA-3-12-AW | 3 | 12 | ● |     | ● |   |   | 0.83 - 1.7  | 10   |
| SWA-3-15-AW | 3 | 15 | ● |     | ● |   |   | 1.3 - 2.7   | 10   |
| SWA-4-8-AW  | 4 | 8  | ● | ●   | ● |   |   | 0.3 - 0.6   | 10   |
| SWA-4-10-AW | 4 | 10 | ● |     | ● | ● |   | 0.53 - 1.6  | 10   |
| SWA-4-12-AW | 4 | 12 | ● |     | ● | ● | ● | 0.8 - 3.9   | 10   |
| SWA-4-15-AW | 4 | 15 | ● |     | ● | ● | ● | 1.3 - 6.4   | 10   |
| SWA-4-16-AW | 4 | 16 | ● |     | ● | ● | ● | 1.5 - 7.4   | 10   |
| SWA-4-18-AW | 4 | 18 | ● |     | ● | ● | ● | 1.9 - 9.5   | 10   |
| SWA-4-20-AW | 4 | 20 |   |     | ● | ● | ● | 4.7 - 12    | 10   |
| SWA-4-25-AW | 4 | 25 |   |     | ● | ● | ● | 7.5 - 19    | 10   |
| SWA-5-8-AW  | 5 | 8  | ● | ●   | ● |   |   | 0.25 - 0.49 | 10   |
| SWA-5-10-AW | 5 | 10 | ● |     | ● | ● |   | 0.47 - 1.4  | 10   |
| SWA-5-12-AW | 5 | 12 | ● |     | ● | ● | ● | 0.74 - 3.7  | 10   |
| SWA-5-15-AW | 5 | 15 | ● |     | ● | ● | ● | 1.2 - 6.2   | 10   |
| SWA-5-16-AW | 5 | 16 | ● |     | ● | ● | ● | 1.4 - 7.1   | 10   |
| SWA-5-18-AW | 5 | 18 | ● |     | ● | ● | ● | 1.8 - 9.2   | 10   |
| SWA-5-20-AW | 5 | 20 | ● |     | ● | ● | ● | 2.3 - 12    | 10   |
| SWA-5-25-AW | 5 | 25 |   |     | ● | ● | ● | 7.4 - 18    | 10   |

● 数量未满1包的订单, 会另外收取手续费。详情请垂询散装零售服务。

单位: mm

| 型号           | d  | D  | t |     |   |   |   | 质量(g)       | 每包数量 |
|--------------|----|----|---|-----|---|---|---|-------------|------|
|              |    |    | 1 | 1.5 | 2 | 3 | 5 |             |      |
| SWA-6-8-AW   | 6  | 8  | ● | ●   | ● |   |   | 0.17 - 0.34 | 10   |
| SWA-6-10-AW  | 6  | 10 | ● |     | ● | ● |   | 0.4 - 1.2   | 10   |
| SWA-6-12-AW  | 6  | 12 | ● |     | ● | ● | ● | 0.68 - 3.3  | 10   |
| SWA-6-15-AW  | 6  | 15 | ● |     | ● | ● | ● | 1.2 - 5.8   | 10   |
| SWA-6-16-AW  | 6  | 16 | ● |     | ● | ● | ● | 1.4 - 6.8   | 10   |
| SWA-6-18-AW  | 6  | 18 | ● |     | ● | ● | ● | 1.8 - 8.9   | 10   |
| SWA-6-20-AW  | 6  | 20 | ● |     | ● | ● | ● | 2.3 - 11    | 10   |
| SWA-6-25-AW  | 6  | 25 | ● |     | ● | ● | ● | 3.6 - 18    | 10   |
| SWA-6-30-AW  | 6  | 30 |   |     | ● | ● | ● | 11 - 27     | 10   |
| SWA-8-12-AW  | 8  | 12 | ● |     | ● | ● | ● | 0.49 - 2.5  | 10   |
| SWA-8-15-AW  | 8  | 15 |   |     | ● | ● | ● | 2 - 5       | 10   |
| SWA-8-16-AW  | 8  | 16 |   |     | ● | ● | ● | 2.4 - 6     | 10   |
| SWA-8-18-AW  | 8  | 18 |   |     | ● | ● | ● | 3.2 - 8     | 10   |
| SWA-8-20-AW  | 8  | 20 |   |     | ● | ● | ● | 4.2 - 10    | 10   |
| SWA-8-25-AW  | 8  | 25 |   |     | ● | ● | ● | 7 - 17      | 10   |
| SWA-8-30-AW  | 8  | 30 |   |     | ● | ● | ● | 10 - 26     | 10   |
| SWA-10-12-AW | 10 | 12 | ● |     | ● | ● | ● | 0.27 - 1.4  | 10   |
| SWA-10-15-AW | 10 | 15 |   |     | ● | ● | ● | 1.5 - 3.8   | 10   |
| SWA-10-16-AW | 10 | 16 |   |     | ● | ● | ● | 1.9 - 4.8   | 10   |
| SWA-10-18-AW | 10 | 18 |   |     | ● | ● | ● | 2.8 - 6.9   | 10   |
| SWA-10-20-AW | 10 | 20 |   |     | ● | ● | ● | 3.7 - 9.3   | 10   |
| SWA-10-25-AW | 10 | 25 |   |     |   | ● | ● | 9.8 - 16    | 10   |
| SWA-10-30-AW | 10 | 30 |   |     |   | ● | ● | 15 - 25     | 10   |
| SWA-10-35-AW | 10 | 35 |   |     |   | ● | ● | 21 - 35     | 10   |
| SWA-10-40-AW | 10 | 40 |   |     |   | ● | ● | 28 - 46     | 10   |
| SWA-10-50-AW | 10 | 50 |   |     |   | ● | ● | 44 - 74     | 10   |
| SWA-12-16-AW | 12 | 16 |   |     |   | ● | ● | 2.1 - 3.5   | 10   |
| SWA-12-18-AW | 12 | 18 |   |     | ● | ● | ● | 2.2 - 5.5   | 10   |
| SWA-12-20-AW | 12 | 20 |   |     | ● | ● | ● | 3.2 - 8     | 10   |
| SWA-12-25-AW | 12 | 25 |   |     |   | ● | ● | 9 - 15      | 10   |
| SWA-12-30-AW | 12 | 30 |   |     |   | ● | ● | 14 - 23     | 10   |
| SWA-12-35-AW | 12 | 35 |   |     |   | ● | ● | 20 - 33     | 10   |
| SWA-12-40-AW | 12 | 40 |   |     |   | ● | ● | 27 - 45     | 10   |
| SWA-12-50-AW | 12 | 50 |   |     |   | ● | ● | 44 - 73     | 10   |
| SWA-16-20-AW | 16 | 20 |   |     | ● | ● | ● | 1.8 - 4.5   | 10   |
| SWA-16-25-AW | 16 | 25 |   |     |   | ● | ● | 6.9 - 11    | 10   |
| SWA-16-30-AW | 16 | 30 |   |     |   | ● | ● | 12 - 20     | 10   |
| SWA-16-35-AW | 16 | 35 |   |     |   | ● | ● | 18 - 30     | 10   |
| SWA-16-40-AW | 16 | 40 |   |     |   | ● | ● | 25 - 41     | 10   |
| SWA-16-50-AW | 16 | 50 |   |     |   | ● | ● | 41 - 69     | 10   |
| SWA-20-35-AW | 20 | 35 |   |     |   | ● | ● | 15 - 25     | 10   |
| SWA-20-40-AW | 20 | 40 |   |     |   | ● | ● | 22 - 37     | 10   |
| SWA-20-50-AW | 20 | 50 |   |     |   | ● | ● | 39 - 65     | 10   |

● 数量未满1包的订单, 会另外收取手续费。详情请垂询散装零售服务。

● 型号指定

SWA-2-8-1-AW



2 t尺寸请从表中标有●的尺寸中选择。