



- 轴承固定用的固定轴环。
- 通过主体的凸部, 仅按压轴承内圈即可固定。
- 最适用于难以在轴上固定扣环等情况下的轴承固定。
- 使用定位螺丝与轴连接。

● 材质、表面处理



	NSC-CB	NSC-MB
主体	S45C 四氧化三铁保护膜(黑)	S45C 无电解 镀镍
内六角 止动螺丝	SCM435 四氧化三铁保护膜(黑)	SUSXM7



单位: mm

型号  四氧化三铁保护膜	型号  无电解镀镍	d	B	B ₁	D	D ₁	M(粗牙)*1	适用 轴承	质量(g)
NSC-3-7-CB	NSC-3-7-MB	3	7.5	5	7	5	M3	693ZZ・623ZZ	1
NSC-4-7-CB	NSC-4-7-MB	4	7.5	5	8	6	M3	694ZZ・624ZZ	2
NSC-5-7-CB	NSC-5-7-MB	5	7.5	5	11	7.2	M3	695ZZ・605ZZ・625ZZ	4
NSC-6-7-CB1	NSC-6-7-MB1	6	7.5	5	13	8.4	M3	606ZZ	4
NSC-6-7-CB2	NSC-6-7-MB2	6	7.5	5	13	9.2	M3	626ZZ	5
NSC-6-7-CB3	NSC-6-7-MB3	6	7.5	5	13	8	M3	696ZZ	6
NSC-8-9-CB1	NSC-8-9-MB1	8	9.5	7	18	11.7	M4	608ZZ	12
NSC-8-9-CB2	NSC-8-9-MB2	8	9.5	7	18	11.4	M4	628ZZ	11
NSC-8-9-CB3	NSC-8-9-MB3	8	9.5	7	18	10.4	M4	698ZZ	11
NSC-10-11-CB1	NSC-10-11-MB1	10	11	8	20	14.2	M5	6000ZZ	16
NSC-10-11-CB2	NSC-10-11-MB2	10	11	8	20	16.7	M5	6200ZZ	18
NSC-10-11-CB3	NSC-10-11-MB3	10	11	8	20	13.2	M5	6900ZZ	15
NSC-12-11-CB1	NSC-12-11-MB1	12	11	8	22	17.2	M5	6001ZZ	19
NSC-12-11-CB2	NSC-12-11-MB2	12	11	8	22	17.7	M5	6201ZZ	19
NSC-12-11-CB3	NSC-12-11-MB3	12	11	8	22	15.2	M5	6901ZZ	17
NSC-15-11-CB1	NSC-15-11-MB1	15	11	8	25	20.2	M5	6002ZZ	22
NSC-15-11-CB2	NSC-15-11-MB2	15	11	8	25	21.2	M5	6202ZZ	23
NSC-15-11-CB3	NSC-15-11-MB3	15	11	8	25	18.7	M5	6902ZZ	21

*1: 附带内六角止动螺丝。

*1: d尺寸5以下时为1处。

单位: mm

型号  四氧化三铁保护膜	型号  无电解镀镍	d	B	B ₁	D	D ₁	M(粗牙)*1	适用 轴承	质量(g)
NSC-17-13-CB1	NSC-17-13-MB1	17	13	10	28	22.2	M6	6003ZZ	33
NSC-17-13-CB2	NSC-17-13-MB2	17	13	10	28	24.2	M6	6203ZZ	35
NSC-17-13-CB3	NSC-17-13-MB3	17	13	10	28	20.2	M6	6903ZZ	31
NSC-20-13-CB1	NSC-20-13-MB1	20	13	10	35	25.2	M6	6004ZZ	52
NSC-20-13-CB2	NSC-20-13-MB2	20	13	10	35	27.2	M6	6204ZZ	54
NSC-20-13-CB3	NSC-20-13-MB3	20	13	10	35	24.7	M6	6904ZZ	52
NSC-25-13-CB1	NSC-25-13-MB1	25	13.5	10	38	31.2	M6	6005ZZ	55
NSC-25-13-CB2	NSC-25-13-MB2	25	13.5	10	38	33.2	M6	6205ZZ	58
NSC-25-13-CB3	NSC-25-13-MB3	25	13.5	10	38	30.2	M6	6905ZZ	54
NSC-30-15-CB1	NSC-30-15-MB1	30	15.5	12	45	38.2	M8	6006ZZ	90
NSC-30-15-CB2	NSC-30-15-MB2	30	15.5	12	45	40.2	M8	6206ZZ	94
NSC-30-15-CB3	NSC-30-15-MB3	30	15.5	12	45	35.2	M8	6906ZZ	86
NSC-35-16-CB1	NSC-35-16-MB1	35	16.5	12	50	43.2	M8	6007ZZ	106
NSC-35-16-CB2	NSC-35-16-MB2	35	16.5	12	50	46.2	M8	6207ZZ	114
NSC-35-16-CB3	NSC-35-16-MB3	35	16.5	12	50	41.2	M8	6907ZZ	101
NSC-40-18-CB1	NSC-40-18-MB1	40	18.5	14	60	48.2	M10	6008ZZ	183
NSC-40-18-CB2	NSC-40-18-MB2	40	18.5	14	60	52.2	M10	6208ZZ	195
NSC-40-18-CB3	NSC-40-18-MB3	40	18.5	14	60	46.2	M10	6908ZZ	179

*1: d尺寸5以下时为1处。

● 型号指定

NSC-4-7-CB



 无尘洗净・无尘包装 → P.xxxx	 螺纹切割 → P.xxxx	 防松动 → P.xxxx	 激光刻印 → P.xxxx
不可对应	不可对应	不可对应	可对应, 费用另计