



- 轴承固定用的固定轴环。
- 通过主体的凸部, 仅按压轴承内圈即可固定。
- 最适用于难以在轴上固定扣环等情况下的轴承固定。
- 使用定位螺丝与轴连接。

材质、表面处理	NSC-SB
主体	SUS304
内六角止动螺丝	SUSXM7



单位 : mm

型号	d	B	B ₁	D	D ₁	M(粗牙)*1	适用 轴承	质量(g)
NSC-3-7-SB	3	7.5	5	7	5	M3	693ZZ・623ZZ	2
NSC-4-7-SB	4	7.5	5	8	6	M3	694ZZ・624ZZ	2
NSC-5-7-SB	5	7.5	5	11	7.2	M3	695ZZ・605ZZ・625ZZ	3
NSC-6-7-SB1	6	7.5	5	13	8.4	M3	606ZZ	4
NSC-6-7-SB2	6	7.5	5	13	9.2	M3	626ZZ	5
NSC-6-7-SB3	6	7.5	5	13	8	M3	696ZZ	4
NSC-8-9-SB1	8	9.5	7	18	11.7	M4	608ZZ	12
NSC-8-9-SB2	8	9.5	7	18	11.4	M4	628ZZ	12
NSC-8-9-SB3	8	9.5	7	18	10.4	M4	698ZZ	11
NSC-10-11-SB1	10	11	8	20	14.2	M5	6000ZZ	16
NSC-10-11-SB2	10	11	8	20	16.7	M5	6200ZZ	18
NSC-10-11-SB3	10	11	8	20	13.2	M5	6900ZZ	16
NSC-12-11-SB1	12	11	8	22	17.2	M5	6001ZZ	19
NSC-12-11-SB2	12	11	8	22	17.7	M5	6201ZZ	19
NSC-12-11-SB3	12	11	8	22	15.2	M5	6901ZZ	18
NSC-15-11-SB1	15	11	8	25	20.2	M5	6002ZZ	22
NSC-15-11-SB2	15	11	8	25	21.2	M5	6202ZZ	23
NSC-15-11-SB3	15	11	8	25	18.7	M5	6902ZZ	21

*1: 附带内六角止动螺丝。

*1: d尺寸5以下时为1处。



单位 : mm

型号	d	B	B ₁	D	D ₁	M(粗牙)*1	适用 轴承	质量(g)
NSC-17-13-SB1	17	13	10	28	22.2	M6	6003ZZ	33
NSC-17-13-SB2	17	13	10	28	24.2	M6	6203ZZ	35
NSC-17-13-SB3	17	13	10	28	20.2	M6	6903ZZ	32
NSC-20-13-SB1	20	13	10	35	25.2	M6	6004ZZ	54
NSC-20-13-SB2	20	13	10	35	27.2	M6	6204ZZ	55
NSC-20-13-SB3	20	13	10	35	24.7	M6	6904ZZ	53
NSC-25-13-SB1	25	13.5	10	38	31.2	M6	6005ZZ	56
NSC-25-13-SB2	25	13.5	10	38	33.2	M6	6205ZZ	59
NSC-25-13-SB3	25	13.5	10	38	30.2	M6	6905ZZ	55
NSC-30-15-SB1	30	15.5	12	45	38.2	M8	6006ZZ	92
NSC-30-15-SB2	30	15.5	12	45	40.2	M8	6206ZZ	95
NSC-30-15-SB3	30	15.5	12	45	35.2	M8	6906ZZ	87
NSC-35-16-SB1	35	16.5	12	50	43.2	M8	6007ZZ	108
NSC-35-16-SB2	35	16.5	12	50	46.2	M8	6207ZZ	116
NSC-35-16-SB3	35	16.5	12	50	41.2	M8	6907ZZ	102
NSC-40-18-SB1	40	18.5	14	60	48.2	M10	6008ZZ	185
NSC-40-18-SB2	40	18.5	14	60	52.2	M10	6208ZZ	196
NSC-40-18-SB3	40	18.5	14	60	46.2	M10	6908ZZ	180

*1: d尺寸5以下时为1处。

- 型号指定

NSC-4-7-SB



无尘洗净・无尘包装 → P.xxxx	螺纹切割 → P.xxxx	防松动 → P.xxxx	激光刻印 → P.xxxx
欢迎洽询	不可对应	不可对应	可对应, 费用另计